

Amphenol PCD SZ
ORIGINAL
PDF Format
R&D


安费诺精密连接器(深圳)有限公司
Amphenol PCD Shenzhen

受 控 文 件


2026年8月11日

C-HVCOCFXXXX1

REV	ECN	DESCRIPTION	DATE	MODIFIED
1		PRE- RELEASE	07-19-23	
2	R7649	UPDATED DRAWING	11-30-23	
3	C10415	UPDATE TORQUE REQUIREMENTS	Jul-14-26	



ELECTRONIC LOCK FIXED POSITION:
AC PART: 3 O'CLOCK OR 9 O'CLOCK
RECOMMENDED:
Amphenol 12V ELOCK
Amphenol 24V ELOCK
(Customers buy separately)



SIGNAL CONNECTOR INFORMATION
REFERENCE DRAWING:C-LVRC10CF020D
C-P08B002343 3P/AC
C-P08B002344 1P/AC
C-P08B002345 NO AC
(Customers buy separately)

TABLE 1 SPECIFICATION AND REQUIREMENTS

NOTE	DESCRIPTION	SPECIFICATION OR REQUIREMENT	
1	HOUSING COLOR	BLACK	
2	CABLE SPEC	COMPLIANT WITH LV216 ;SEE TABLE 2	
3	INSULATION RESISTANCE(NORMAL CLIMATE)	MIN. 100 MΩ	
4	MAX. RATING CURRENT	SIGNAL:2A AC:32A FOR 6 SQUARE CABLE;63A FOR 16 SQUARE CABLE DC:150A-300A	+
5	MAX. RATING VOLTAGE	SIGNAL: 30 VDC AC: SINGLE PHASE 250 VAC, 3 PHASE 480 VAC DC: 1000 VDC	+
6	DIELECTRIC WITHSTAND VOLTAGE	SIGNAL: 500 VAC / 60 S AC: 2000 VAC / 60 S DC: 3000 VAC / 60 S	+
7	OPERATING AMBIENT TEMPERATURE	-30 °C ~ +50°C	+
8	MAX. WORKING TEMPERATURE	90 °C	⊙
9	TEMPERATURE SENSOR TYPE	PT1000/NTC FOR DC;PT1000/NTC FOR AC	
10	MOUNTING TORQUE FOR M6 NUT	5.3±0.5 N.m	⊙
11	MOUNTING TORQUE FOR LVRC/ AC FERRULE	0.9±0.1 N.m	⊙
12	MOUNTING TORQUE FOR DC FERRULE	0.9±0.1 N.m	⊙
13	MOUNTING TORQUE FOR ELOCK//BACK COVER	0.7±0.035N.m	⊙
14	DEGREE OF PROTECTION	INLET:IP67 WITH COVER:IP55 MATED:IP54	+
15	ASSEMBLY METHOD FOR SCREENING BRAID OF CABLES	ENTER INTO THE CONNECTOR	
16	MATING CYCLES (UNLOADED)	REFER TO IEC 62196 2022	⊙
17	NEUTRAL SALT SPRAY TEST	240H, NOT OCCUR RED CORROSION.	
18	IEC STANDARD	REFER TO IEC 62196-1,2,3	
19	CHARGING MODE	MODE 2/3/4	+
20	ROHS COMPLIANCE	YES	
21	RECOMMENDED HOLE LAYOUT IN MOUNTING PANEL	SEE FIGURE 1	+
22	CONNECTING METHOD FOR TERMINALS	CRIMP	
23	LED INDICATOR LIGHT	NA	

HVCOCFX XX X I MODEL SELECTION:

C-1-PHASE
D-3-PHASE
BLANK FOR NO AC

01-DC300A/AC63A
02-DC300A/AC32A
03-DC300A/WITHOUT AC
04-DC250A/AC63A
05-DC250A/AC32A
06-DC250A/WITHOUT AC
07-DC200A/AC63A
08-DC200A/AC32A
09-DC200A/WITHOUT AC
10-DC150A/AC63A
11-DC150A/AC32A
12-DC150A/WITHOUT AC

A-TEMPERATURE SENSOR MODEL DC PT1000+AC NTC
B-TEMPERATURE SENSOR MODEL DC PT1000+AC PT1000
C-TEMPERATURE SENSOR MODEL DC PT1000+NO AC
D-TEMPERATURE SENSOR MODEL DC NTC+AC NTC
E-TEMPERATURE SENSOR MODEL DC NTC+AC PT1000
F-TEMPERATURE SENSOR MODEL DC NTC+NO AC


WITHOUT LED

RECOMMENDED MODEL :

HVCOCFCI1A1:DC 150 A ;AC32A 1PHEASE
HVCOCFDI1A1:DC 150 A ;AC32A 3PHEASE
HVCOCFC08A1:DC 200 A ;AC32A 1PHEASE
HVCOCFD08A1:DC 200 A ;AC32A 3PHEASE
HVCOCFC05A1:DC 250 A ;AC32A 1PHEASE
HVCOCFD05A1:DC 250 A ;AC32A 3PHEASE
HVCOCFC02A1:DC 300 A ;AC32A 1PHEASE
HVCOCFD02A1:DC 300 A ;AC32A 3PHEASE

RECOMMENDED PURCHASE COMBINATION:
I.C-HVCOCFXXXX1+C-P08B002343(4)(5)+C-P02B000051+Amphenol E-LOCK

PRINTING INFORMATION:




VARIES ACCORDING TO DIFFERENT MODELS:
PRINTING 1:
XP: 1P
XXXVAC XXA:250VAC 32A/63A
XXXXV DC XXXA:1000VDC 150A/200A/250A/300A
XP: 3P
XXXVAC XXA:480VAC 32A/63A
XXXXV DC XXXA:1000VDC 150A/200A/250A/300A

PRINTING 2 (NO AC PART):
NO"PHASE:XP"" XXXV AC"PRINTING
XXXXV DC XXXA:1000VDC 150A/200A/250A/300A


DIMENSIONS	TOLERANCES	PROJECTION	TITLE				
ANSI Y14.5M	.X ±0.5		CCS2 SOCKET-WITHOUT LED				
UNITS: MM	.XX ±0.05						
Pro/E FILE	ANGLES ±2°		ENGR	Feb-08-23			
ORIGINAL	THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION WHICH IS THE CONFIDENTIAL PROPERTY OF Amphenol PCD Shenzhen Co. Ltd Amphenol PCD Shenzhen Co. Ltd RESERVES THE RIGHT TO CLARIFY THIS DRAWING	CHKD	rock.chen		SIZE	DWG NO.	REV
		APPD	Jock		A3	C-HVCOCFXXXX1	3
				SCALE: 3:1		SHEET 1 OF 4	

C-HVCOCFXXXX1


1-PHASE AC CHARGING AND DC CHARGING



3-PHASE AC CHARGING AND DC CHARGING



NO AC CHARGING AND DC CHARGING



安费诺精密连接器(深圳)有限公司
Amphenol PCD Shenzhen

受 控 文 件

2026年8月11日

SIZE	DWG NO.	REV
A3	C-HVCOCFXXXX1	3
SCALE: 3:1		SHEET 2 OF 4

C-HVCOCFXXXXX1



CABLE APPLIED	CONDUCTOR SIZE mm ²	O.D. OF CABLE mm	MAX. RATING CURRENT A
AC CABLE	6	6.25±0.25	32
	16	9.9±0.3	63
DC CABLE (Recommended tinned wire)	35	14.1±0.3	150
	50	15.5±0.3	200
	70	17.8±0.4	250
	95	20.5±0.4	300
PE CABLE	25	9.6±0.2	N/A
SIGNAL CABLE	0.5 TO 0.75	1.5 TO 1.9	2

SIZE A3	DWG NO. C-HVCOCFXXXX1	REV 3
SCALE: 3:1		SHEET 3 OF 4

C-HVCOCFXXXX1

NTC TEMPERATURE SENSOR TABLE 3

PARAMETER	SPECIFICATION AND REQUIREMENT
RESISTANCE VALUE AT 25°C	10KΩ
TOLERANCE ON R ₂₅ -VALUE	±1%
OPERATING TEMPERATURE RANGE	-40°C TO +150 °C
B _{25°C/85°C} -VALUE	3960K
TOLERANCE ON B _{25°C/85°C} -VALUE	±1%
RESPONSE TIME(63.2%) 25°C TO 85°C STIRRED AIR (FOR INFO)	≈8 s
DISSIPATION FACTOR *IN STILL AIR (FOR INFO)	3.0 mW
MAXIMUM POWER DISSIPATION AT 25°C	125 mW
TEMPERATURE COMPENSATION VALUE RELATIVE TO ACTUAL TEMPERATURE	TBD
R-T VALUE	REFER TO R-T INDEXING TABLE IN TABLE 4
T(R _{NTC})=90 °C	THE CHARGE CURRENT MUST BE REDUCED IN ORDER TO PREVENT FURTHER INCREASE OF TEMPERATURE AT THE CONTACTS.
T(R _{NTC})=100 °C	CHARGING PROCESS HAS TO BE SHUT DOWN!

TABLE 4 R-T INDEXING TABLE FOR NTC

Temp.(°C)	Rnom(kΩ)	Rmin(kΩ)	Rmax(kΩ)
-50	689.93622	619.1557	760.7168
-40	347.11639	317.0853	377.1474
-30	182.02324	168.9417	195.1048
-20	99.31278	93.5065	105.1191
-10	56.25714	53.6606	58.8537
0	33.00928	31.8602	34.1584
10	20.01506	19.5282	20.5019
20	12.51234	12.3296	12.6950
30	8.04676	7.9484	8.1451
40	5.31252	5.2251	5.3999
50	3.59362	3.5202	3.6670
60	2.48617	2.4261	2.5462
70	1.75621	1.7076	1.8048
80	1.26473	1.2255	1.3039
90	0.92723	0.8941	0.9603
100	0.69116	0.6623	0.7200
110	0.52320	0.4984	0.5480
120	0.40176	0.3805	0.4230

安费诺精密连接器(深圳)有限公司

Amphenol PCD Shenzhen

受 控 文 件

2026年8月11日

PT1000 TEMPERATURE SENSOR TABLE 5

PARAMETER	SPECIFICATION AND REQUIREMENT
STANDARD	DIN EN 60751
TOLERANCE	CLASS 2B(R ₀ :±0.24%)
OPERATING TEMPERATURE RANGE	-50 °C TO +130 °C
TEMPERATURE COEFFICIENT	TCR=3850 ppm/K
MEASURING CURRENT	0.1 TO 0.3 mA
SELF HEATING	0.8 K/mW at 0°C
REACTION TIME	<3 s TBD
TEMPERATURE COMPENSATION VALUE RELATIVE TO ACTUAL TEMPERATURE	TBD
R-T VALUME	REFER TO R-T INDEXING TABLE IN TABLE 6
T(R _{PT1000})=90 °C	THE CHARGE CURRENT MUST BE REDUCED IN ORDER TO PREVENT FURTHER INCREASE OF TEMPERATURE AT THE CONTACTS.
T(R _{PT1000})=100 °C	CHARGING PROCESS HAS TO BE SHUT DOWN!

TEMPERATURE	0	+1	+2	+3	+4	+5	+6	+7	+8	+9
-50	803.08	807.05	811.02	814.98	818.95	822.91	826.88	830.84	834.80	838.76
-40	842.72	846.67	850.63	854.58	858.54	862.49	866.44	870.39	874.33	878.28
-30	882.22	886.17	890.11	894.05	897.99	901.93	905.87	909.80	913.74	917.67
-20	921.60	925.54	929.47	933.39	937.32	941.25	945.17	949.10	953.02	956.94
-10	960.86	964.78	968.70	972.62	976.53	980.45	984.36	988.27	992.18	996.09
0	1000.00	1003.91	1007.81	1011.72	1015.62	1019.53	1023.43	1027.33	1031.23	1035.13
10	1039.02	1042.92	1046.81	1050.71	1054.60	1058.49	1062.38	1066.27	1070.16	1074.04
20	1077.93	1081.81	1085.70	1089.58	1093.46	1097.34	1101.22	1105.10	1108.97	1112.85
30	1116.72	1120.59	1124.47	1128.34	1132.21	1136.07	1139.94	1143.81	1147.67	1151.53
40	1155.40	1159.26	1163.12	1166.98	1170.84	1174.69	1178.55	1182.40	1186.25	1190.11
50	1193.96	1197.81	1201.66	1205.50	1209.35	1213.19	1217.04	1220.88	1224.72	1228.56
60	1232.40	1236.24	1240.08	1243.91	1247.75	1251.58	1255.41	1259.25	1263.08	1266.90
70	1270.73	1274.56	1278.38	1282.21	1286.03	1289.85	1293.67	1297.49	1301.31	1305.13
80	1308.95	1312.76	1316.58	1320.39	1324.20	1328.01	1331.82	1335.63	1339.43	1343.24
90	1347.02	1350.85	1354.65	1358.45	1362.25	1366.05	1369.85	1373.65	1377.44	1381.23
100	1385.03	1388.82	1392.61	1396.40	1400.19	1403.98	1407.76	1411.55	1415.33	1419.11
110	1422.90	1426.68	1430.46	1434.23	1438.01	1441.79	1445.56	1449.33	1453.11	1456.88
120	1460.65	1464.42	1468.18	1471.95	1475.72	1479.48	1483.24	1487.01	1490.77	1494.53
130	1498.28	1502.04	1505.80	1509.55	1513.31	1517.06	1520.81	1524.56	1528.31	1532.06

SIZE

DWG NO.

C-HVCOCFXXXX1

REV

3

SCALE: 3:1

SHEET 4 OF 4